



US008718150B2

(12) **United States Patent**
Kanterakis et al.

(10) **Patent No.:** **US 8,718,150 B2**
(45) **Date of Patent:** **May 6, 2014**

(54) **RACH-RAMP-UP ACKNOWLEDGEMENT**

(75) Inventors: **Emmanuel Kanterakis**, North Brunswick, NJ (US); **Kourosh Parsa**, Riverside, CT (US)

(73) Assignee: **Golden Bridge Technology, Inc.**, Long Branch, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 913 days.

(21) Appl. No.: **12/390,860**

(22) Filed: **Feb. 23, 2009**

(65) **Prior Publication Data**

US 2009/0161635 A1 Jun. 25, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/979,117, filed on Oct. 31, 2007, now Pat. No. 7,508,861, which is a continuation of application No. 10/412,576, filed on Apr. 14, 2003, now Pat. No. 7,359,427, which is a continuation of application No. 09/273,450, filed on Mar. 22, 1999, now Pat. No. 6,574,267.

(51) **Int. Cl.**

H04L 27/00 (2006.01)

(52) **H04L 23/00** (2006.01)

USPC **375/259**; 375/377; 370/447

(58) **Field of Classification Search**

CPC H04W 28/22; H04W 28/26; H04W 52/00; H04W 72/0466; H04W 74/00; H04W 74/002; H04W 74/004; H04W 74/08; H04W 74/0833; H04W 74/0841; H04W 74/085; H04B 1/7075; H04B 7/2628

USPC 375/130, 140-147, 149-152, 362-368, 375/377, 358; 370/328, 335, 342, 345, 347, 370/442, 445, 218, 525-529, 503, 278, 370/441; 455/515, 516, 450, 509, 517, 513, 455/500

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,689,786 A 8/1987 Sidhu et al.
5,103,459 A 4/1992 Gilhousen et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 731 578 9/1996
EP 0731578 A2 9/1996

(Continued)

OTHER PUBLICATIONS

United States Court of Appeals for the Federal Circuit, *Golden Bridge Technology, Inc. v. Nokia, Inc. and Lucent Technologies, Inc.*, Appeal from the United States District Court for the Eastern District of Texas in Case No. 2:02-CV-151, Judge Leonard Davis, Reply Brief for Plaintiff-Appellant Oct. 29, 2007, 2007-1215.

(Continued)

Primary Examiner — Tesfaldet Bocure

(74) *Attorney, Agent, or Firm* — McCarter & English, LLP

(57)

ABSTRACT

A disclosed code-division-multiple-access (CDMA) system has a base station (BS) and remote stations (RSs). A BS-spread-spectrum transmitter broadcasts a common-synchronization channel having a chip-sequence signal common to the remote stations served by the BS, and a frame-timing signal. A RS-spread-spectrum receiver receives the broadcast common-synchronization channel, and determines frame timing from the frame-timing signal. A first RS-spread-spectrum transmitter transmits an access-burst signal, which has a plurality of segments. Each access burst signal segment has a plurality of power levels. A BS-spread-spectrum receiver receives the access-burst signal at a detected-power level. In response to receiving the access-burst signal, a BS-spread-spectrum transmitter transmits an acknowledgment signal to the RS-spread-spectrum receiver. The RS-spread-spectrum receiver receives the acknowledgment signal, and in, the RS-spread-spectrum transmitter transmits a spread-spectrum signal having data to the BS-spread-spectrum receiver.

97 Claims, 11 Drawing Sheets

